Cabinet/Closet Knobs and Pulls

513 Knob Backplate

- For use with Ives cabinet knobs 521, 523, 524, 530 and 535.
- Available in two diameters: 1-1/2" and 1-3/4".
- Provides a finishing touch. Especially useful to cover holes or marks in replacement or remodeling applications.
- Made from wrought brass.
- 3/64" thick backplate. (This increases the projection of knob or pull.)
- Conforms to ANSI/BHMA A156.9 B22181.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Models:
513 1 1/2IN
513 1 3/4IN

521 Round Knob

- Available in four diameters: 3/4", 1", 1-1/4" and 1-1/2".
- Made from wrought brass.
- Furnished with a No. 8-32 machine screw, 1-1/8" long.
- Conforms to ANSI/BHMA A156.9 B22131.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Model & Diameter	Projection
521 3/4IN	3/4"
521 1IN	15/16"
521 1 1/4IN	1-1/8"
521 1 1/2IN	1-5/16"

523 Colonial Knob

- Available in four diameters: 5/8", 1", 1-1/4" and 1-1/2".
- Made from wrought brass.
- Furnished with a No. 8-32 machine screw.
- Conforms to ANSI/BHMA A156.9 B22131.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Model & Diameter	Projection	Screw Length
523 5/8IN	5/8"	1"
523 1IN	15/16"	1-1/8"
523 1 1/4IN	1"	1-1/8"
523 1 1/2IN	1-7/32"	1-1/8"

Cabinet/Closet Knobs and Pulls

524 Round Knob

- Available in five diameters: 5/8", 3/4", 1", 1-1/4" and 1-1/2".
- Made from wrought brass. 1",1-1/4" and 1-1/2" diameter knobs also made from anodized aluminum or epoxy-coated aluminum.
- Furnished with a No. 8-32 machine screw.
- Conforms to ANSI/BHMA A156.9 B22131 for brass, B42131 for aluminum.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D. 1", 1 1/4" and 1 1/2" knobs also available in PA-A (almond), PA-W (white), PA-BLK (black).

Model & Diameter	Projection	Screw Length
524 5/8IN	5/8"	1"
524 3/4IN	23/32"	1-1/8"
524 1IN	7/8"	1-1/8"
524 1 1/4IN	1-1/32"	1-1/8"
524 1 1/2IN	1-7/32"	1-1/8"

530 Ball Knob

- Available in two diameters: 1" and 1-1/4".
- Made from wrought brass.
- Furnished with a No. 8-32 machine screw.
- Conforms to ANSI/BHMA A156.9 B22131.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.

Model & Diameter	Projection	Screw Length
530 1IN	1-1/4"	1-1/8"
530 1 1/4IN	1-1/2"	1-1/8"

535 Oval Knob

- Available in two sizes: 1-1/8" and 1-3/8".
- Made from wrought brass.
- Furnished with a No. 8-32 machine screw.
- Conforms to ANSI/BHMA A156.9 B22131.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.

Model & Size (Height)	Knob Width	Projection	Screw Length
535 1 1/8IN	13/16"	1-5/32"	1-1/8"
535 1 3/8IN	1"	1-3/8"	1-1/8"

Cabinet/Closet Knobs and Pulls

33/34 Wire Pull

- Made from wrought brass.
- Furnished with No. 8-32 machine screws, 1" long.
- Conforms to ANSI/BHMA A156.9 B22011.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.

Model	Center-to-Center	Overall Size	Projection
33	5"	5-5/16"	1-5/16"
34	6"	6-5/16"	1-5/16"

36/37/38 Wire Pull

- Made from wrought brass, aluminum, or epoxy-coated aluminum.
- Furnished with a No. 8-32 machine screw, 1" long.
- Conforms to ANSI/BHMA A156.9 B22011 for brass, B42011 for aluminum.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D, PA28, PA-A (almond), PA-W (white), PA-BLK (black).

Model	Center-to-Center	Overall Size	Projection
36	3"	3-5/16"	1-5/16"
37	3-1/2"	3-13/16"	1-5/16"
38	4"	4-5/16"	1-5/16"

133 Beaded Pull

- Available in three center-to-centers: 3", 3-1/2", and 4".
- Made from wrought brass.
- Furnished with a No. 8-32 machine screw, 1" long.
- 133 3IN and 133 3-1/2IN are packaged with base washers 504.
- Conforms to ANSI/BHMA A156.9 B22011 for brass.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.

Model	Center-to-Center	Overall Size	Projection
133	3IN	3-3/8"	1-1/8"
133	3 1/2IN	3-7/8"	1-1/8"
133	4IN	4-3/8"	1-1/8"

Cabinet/Closet Knobs and Pulls

137 Drawer Pull

- Made from cast brass or aluminum.
- Furnished with a No. 8-32 machine screw, 1" long.
- Conforms to ANSI/BHMA A156.9 B12011 for brass and 42011 for aluminum.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D, PA28.

Model	Center-to-Center	Overall Size	Projection
137	3"	3-1/2"	7/8"

504 Wire Pull Base Washers

- For use with Ives 33, 34, 36, 37, 38, 133-3IN and 133-3-1/2IN wire pulls.
- Made from wrought brass.
- 5/8" diameter.
- 3/64" thickness (This increases the projection of pull.)
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.

540 Cupboard Latch

- For cabinets or small doors.
- Surface applied, making installation simple.
- Made from cast brass.
- Conforms to ANSI/BHMA A156.9 B13243.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D.



Dimensions:
Case: 1-3/4" x 1-3/16"
Strike: 1-3/4" x 7/16"

2 Elbow Catch

- Ideal for use on the inactive leaf of a pair of cabinet doors.
- Surface applied, making installation simple.
- Made from cast brass or cast aluminum.
- Conforms to design requirements of ANSI/BHMA A156.9.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B26, B26D, A3, A4, A5, A10, A14, A92.

Dimensions:
Plate: 1-3/8" x 5/8"
Strike: 13/16" x 5/8"

Cabinet/Closet Knobs and Pulls

22 Flush Pull

- Low profile makes this pull ideal for louvered, bi-folding or wardrobe doors.
- Extra deep recess and reverse tapered grip provide for ease of pulling and gripping.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15 (B-619), B15A (B-620), B19, B26 (B-625), B26D, B-619, B-620, B-625.



Dimensions:
1-5/16" H x 3-1/8" W x 7/16" D

218 Finger Pull

- Ideal for use on sliding doors.
- Easy installation.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
Inside Cup Diameter: 3/4"
Overall Diameter: 1"
Depth: 5/16"

220/221 Flush Pull

- Ideal for use on sliding doors.
- Built-in prong design eliminates the need for screws or brads and facilitates installation.
- Packed with two escutcheon pins for added holding power.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
220 Inside Cup Diameter: 2"
220 Overall Diameter: 2-3/8"
220 Depth: 7/16"
221 Inside Cup Diameter: 2-1/8"
221 Overall Diameter: 2-7/16"
221 Depth: 7/16"

Cabinet/Closet Knobs and Pulls

222 Flush Pull

- Low profile makes this pull ideal for louvered, bi-folding or wardrobe doors.
- Reverse tapered grip provide for ease of pulling.
- Made from cast brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B12201 and A156.14 D1781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.



Dimensions:
3-1/8" H x 1-5/8" W x 7/16" D

223 Flush Pull

- Low profile makes this pull ideal for louvered, bi-folding or wardrobe doors.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
3-9/16" H x 1-5/16" W x 1/2" D

225/226 Flush Pull

- Ideal for use on sliding doors.
- Easy installation.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- 225 packed with brads; 226 packed with screws.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
225 Inside Cup Diameter: 1-1/2"
225 Overall Diameter: 1-3/4"
225 Depth: 3/8"

226 Inside Cup Diameter: 2-1/8"
226 Overall Diameter: 2-1/2"
226 Depth: 7/16"

227 Flush Pull

- Contoured for ease of pulling.
- Extra deep well.
- Deluxe quality.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201 and A156.14 D2781.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
3-5/8" H x 1-3/4" W x 9/16" D

Cabinet/Closet Knobs and Pulls

425/426 Flush Ring Pull

- Ideal for use on sliding doors.
- Convenient finger grip provides easy use of pull.
- Made from wrought brass.
- Conforms to design requirements of ANSI/BHMA A156.9 B22201.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
425 Inside Cup Diameter: 1-1/2"
425 Overall Diameter: 1-3/4"
425 Depth: 3/8"

426 Inside Cup Diameter: 2-1/8"
426 Overall Diameter: 2-1/2"
426 Depth: 3/8"

42 Pocket Sliding Door Bolt

- Exclusive Ives design permits emergency release of bolt from outside the door.
- Spring activated design allows feather-touch action.
- Brass grommet supplied to cap release hole, protecting the door's finish.
- Made from wrought brass.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
Overall Size, Plate: 3-1/16" x 1-5/32"
Strike: 1" x 3/4"
Depth of Mortise: 5/8"

230 Sliding Door Edge Pull

- 3/4" width allows installation on narrow as well as standard doors.
- Spring automatically returns lever flush with plate.
- Made from solid brass.
- Conforms to design requirements of ANSI/BHMA A156.14 D2801.
- Finishes: B3, B4, B5, B10, B10B, B14, B15, B15A, B19, B26, B26D.

Dimensions:
3-7/8" H x 3/4" W

Cabinet/Closet Knobs and Pulls

990 Sliding Door Pull

- Fits doors 1-3/8" to 1-1/2".
- Decorative coined edges.
- Pre-assembled for doors opening left to right. Plates are reversible.
- Body and strike made from solid brass.
- Finishes: B3, B5, B26, B-613, B-619, B-620.

Dimensions:
1-3/4" deep x 2-1/4" high

991 Sliding Door Lock

- Fits doors 1-3/8" to 1-1/2".
- Decorative coined edges.
- Pre-assembled for doors opening left to right. Plates are reversible.
- Body, turn knob and strike made from solid brass.
- Finishes: B3, B5, B26, B-613, B-619, B-620.

Dimensions:
1-3/4" deep x 2-1/4" high

992 Double Sided Sliding Door Lock

- Fits doors 1-3/8" to 1-1/2".
- Decorative coined edges.
- Pre-assembled for doors opening left to right. Plates are reversible.
- Body, turn knobs and strike made from solid brass.
- Finish: B3.

Dimensions:
1-3/4" deep x 2-1/4" high