LOCKNETICS® by SCHLAGE

400 Series Electromechanical Locks

442S

405 PowerBolt

406S PowerBolt

442S Cabinet Lock
The 442S is a fail secure, solenoid driven cabinet lock. It can be mounted horizontally or vertically to control access to a cabinet. The 442S can be controlled by any kind of access control system that provides a dry contact output. Its small size and versatile mounting position make it ideal for many applications for controlling access to a small opening.

A battery powered (443BP) cabinet lock is also available.

405 PowerBolt
The 405 PowerBolt is a mortise, right angle deadbolt with a 3/4" bolt and a 3/4" throw. It is available fail safe (standard) or fail secure (405S). Additional applications include top and bottom rail doors and all glass doors with the HDB405 herculite door bracket for 1/2" or 3/4" glass doors with no top rail.

406S PowerBolt
The 406S PowerBolt is a fail secure, mortise right angle deadbolt with a 3/4" bolt and 3/4" throw.

LOCKNETICS® by SCHLAGE

400 Series Electromechanical Locks

How To Order 400 Series Electromechanical Locks

405 – DBS – HDB405

Select Model
Select Option
Select Accessories

1. Select Model

PowerBolts

405	Rectangular Front, Fail Safe
405S	Rectangular Front, Fail Secure
406S	Rectangular Front, Fail Secure

Cabinet Locks

442S	Fail Secure

Fail Secure Lock – Requires power to unlock
Fail Safe Lock – Requires power to lock

2. Select Options

PowerBolts

ARSB	Auto Relock Switch (ball type mechanical) 1A @ 120VAC or 28VDC
ARSM	Auto Relock Switch (Magnetic type) 200mA @ 12 VAC/VDC 100mA @ 24 VAC/VDC
BPS	Bolt Position Switch SPDT 7A @ 250VAC
DSB	Door Status Switch (Ball type mechanical) SPDT 1A @ 120 VAC or 28 VDC
DSM	Door Status Monitor (magnetic type)
RC1	Rectifier with filter (for AC voltage operation) Input: 12/24VAC Output:1A @ 12/24 VDC

Note: Ball type mechanical options cannot be ordered with magnetic type options.

Cabinet Lock

RCP	Rectifier (external module) for 442S only

3. Select Accessories

HDB405	U bracket for 1/2" or 3/4" glass door (for 405, 405S only)
MT	Mounting tabs (for 405, 405S only)

Specifications:

PowerBolts

Input Voltage:	12/24 VDC Dual voltage, field selectable
Current Draw:	.9A @ 12VDC .45A @ 24VDC

405/405S

Bolt Size	3/4" diameter 3/4" throw
Overall Size*	8" x 1½" x 1⅝"

406

Bolt Size	3/4" diameter 3/4" throw
Overall Size*	10" x 1 1½" x 1⅝"

*Depth from face of plate

Cabinet Lock 442S

Input Voltage:	12/24VDC Dual Voltage, field selectable
Current Draw:	.5A @ 12VDC .25A @ 24VDC

442S

Overall Size	3" x 1" x 1"

Questions? Call: 866-322-1237 • FAX: 866-322-1233 • Visit us on the Internet at www.locknetics.com
IR Security & Safety Electronic Access Control • 575 Birch Street • Forestville, CT 06010

IR Security & Safety